

PV-500EVO2

Full HD 3" Touch Screen DVR

Now in H.264 Compression!



Feature

- * *Touch screen operation and IR remote control*
- * *High Definition Real 1080P, Frame counter and time stamp functionality*
- * *Digital and Analog Camera Duo Input*
- * *2 Mega Pixel camera compatible*
- * *Continuous/Motion Detect/Prevent/Schedule/Over Write Recording Modes*
- * *User friendly user interface*
- * *Snap-shot functionality*
- * *Multiple password protection*

Specification

Item Number	PV-500EVO2
Display	3.0" 960 x 240 TFT LCD
Video Input	NTSC/ PAL Auto-Detection NTSC/ PAL by UI setting (1.3Mega) / (2Mega)
Video Recording Mode	Standard/Motion Detection/Schedule/Pre-Event/Pre-Motion
Resolution Mode	320x240 to Max 1920x1080 Real Time
Max. Resolution	Above 720P (1280x960) 1080P(1920x1080)
Memory Type	SD Card (Supports up to 32GB SDHC)
Frame Rate	1, 5, 10, 15, 25, 30 fps Adjustable
DC5V to 2.5 Ø phone jack	300mA Max
DC3.3V to mini-HDMI	250mA Max
PC Interface	USB2.0
Image Quality (Bit rate)	In Standard 720x576@25 FPS (PAL) High (5Mbps) / Medium (3.3Mbps) / Low (2.5Mbps) Adjustable
Date/Time Table	YYYY/MM/DD (America) , HH,MM,SS (U.K.)
Frame Counter Stamp	Yes
Picture Format	Baseline JPEG
Power Consumption	Video Playback:480mA Recording:600mA
Battery Life	200min (with BA-2200)
Dimension	85X54X17mm
Weight	71g

*Specifications are subject to change without prior notice.

Standard Accessories

PI-PV800




IR Controller

S-USB/PV-500




USB Cable

CHG-0520



DC 5V Charger

PT-PV800



Pouch

S-EP/PV500




Earphone

BA-2200



2200mA Battery

S-PJ2R-5V



AV In Cable

S-1R3R/PV-500



AV Out Cable

Q-PI-WSD10



Cable Controller

S-MINI HDMI(WDS)



Controller Cable

Optional Accessories

BCM-DU01



Dual Battery Charger

BA-4400



4400mA Battery

Note

The HDMI port is applicable to **CMD-BU13LX** only. PV-500EVO2 is not backward compatible with earlier cameras, CMD-BU13 and CMD-ER13.